

CORELESS INDUCTION FURNACE



- 1. Cover:**
- CALDE® CAST F 65 with CALDE® ANCHORING SYSTEM


- 2. Top cap and spout:**
- CALDE® PATCH PB 82 U for modelling or quick-drying castable CALDE® CAST NB 82 QD as well as READY-SHAPE solutions for top-to-bath

- 3. Hot face:**
- SILICA MIX 5 or 7 for iron alloys, also available as boron-free
 - CALDE® MIX SC 4010 or CALDE® MIX SC 85 M17 for steel and other high-melting alloys
 - SILICA MIX B Cu 7 for Copper based alloys

- 4. Repairs:**
- Pure silica based CALDE® PATCH HQ 22 U or carbon containing SILICA PATCH HQ 26 UC
 - CALDE® STIX F 55 G3 for spout and top cap repairs

- 5. Coil Grout:**
- CALDE® STIX T 90 G1 for classic troweling or self-flowing CALDE® FLOW UT 92 with MICA or COMBI FOIL as slip plane

- 6. Support rings:**
- CALDE® CAST LX 58 as long-lasting standard castable solution or CALDE® SOL CAST M 60 2CP as sol-bonded alternative



CALDERYS also offers various equipment such as vibrators or dust-free installation machines as well as special coatings of the CALDE® SHIELD range that protect your lining against Zinc vapor deposition

EQUIPMENT SPECIFICATIONS

PRODUCT NAME	Grain Size	Temp Limit	Yield (kg / dm ³)	Al ₂ O ₃	SiO ₂	SiC
CALDE® CAST F 65	6mm	1460	2.30	64	30	
CALDE® PATCH PB 82 U	5mm	1600	2.90	82	9	
CALDE® CAST NB 82 QD	6mm	1650	2.75	82	14	
SILICA MIX 5 Pure	6mm	1700	2.20		99	
SILICA MIX 7 Pure	7mm	1700	2.20		99	
CALDE® MIX SC 4010	6mm	1800	3.00	89		
CALDE® MIX SC 85 M17	6mm	1800	3.05	84	0.3	
SILICA MIX B Cu 7	7mm	1580	2.24		90	7
CALDE® PATCH HQ 22 U	4mm	1700	2.20	3	96	
SILICA PATCH HQ 26 UC	4mm	1650	2.20	3	94	
CALDE® STIX F 55 G3	3mm	1450	1.85	55	36	
CALDE® STIX T 90 G1	1mm	1750	2.85	91	3	
CALDE® FLOW UT 92	3mm	1750	2.90	92	7	
CALDE® CAST LX 58	6mm	1650	2.50	57	38	
CALDE® SOL CAST M 60 2CP	6mm	1650	2.50	60	37	

DISCLAIMER: CALDERYS does not warrant the accuracy, fitness for purpose or update of any information disclosed herein. The recipient shall refer to the present content as indicative only. For any instructions or advice, please address formal request to CALDERYS. This document and the information contained herein are the exclusive property of CALDERYS. Reproduction, alteration, copy, release, publication or distribution, in whole or in part, is not allowed. References, trademarks and specifications of the products may vary according to the geographical area to be supplied. For any inquiries regarding supply of products, please liaise with CALDERYS nearest sales area manager.